

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/018936 A1

(51) International Patent Classification⁷: **B41F 27/10, 5/24**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/IT2003/000516

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(22) International Filing Date: 25 August 2003 (25.08.2003)

(25) Filing Language: Italian

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): OFFICINE CURIONI S.p.A. [IT/IT]; Strada per Quartiano, I-26832 Galgagnano LO (IT).

Published:

— *with international search report*


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): MARCHINI, Giorgio [IT/IT]; Seconda Strada, 6, I-20090 Seregno MI (IT).

(74) Agents: CONCONE, Emanuele et al.; Società Italiana Brevetti S.p.A., Via Carducci, 8, I-20123 Milano MI (IT).

(54) Title: PRINTING MACHINE WITH EXTENSIBLE PRINT CYLINDER FOR EASY CHANGE OF THE PRINT SLEEVE



WO 2005/018936 A1

(57) Abstract: A printing machine to work corrugated board and the like includes a print cylinder provided with radial holes (E, E') for emitting compressed air in order to allow the introduction and removal of a print sleeve (S) carrying a print cliché (C), said print cylinder consisting of a fixed shaft (F) on which there is airtightly slidably mounted a mobile cylinder (M) carrying said print sleeve (S), the print cylinder being supported at one end by a dismountable flange with a removable part (R) and by a piston (L) suitable to engage a corresponding seat so to allow the axial movement of said mobile cylinder (M) between a retracted work position and an extended sleeve change position, in which it projects through the machine side to make the change easier, simply by means of the same compressed air used to replace the print sleeve (S).